

## Description

Method and network node for self-regulating, autonomous and decentralized traffic distribution in a multipath network

5

The invention relates to a method for redistributing traffic in response to a traffic overload or a link failure and a node for a packet-based network with multipath distribution.

- 10 Possibly the most important development at present in the field of networks is the development of new technologies to make packet-oriented data networks and thereby primarily the internet suitable for new services. These new services relate primarily to so-called real-time traffic, e.g. voice data and
- 15 video data.

- The success of the internet as the most widely used medium for sending or transmitting data is largely due to its flexibility. IP (Internet Protocol) technology is used for so-called
- 20 destination based routing. IP packets contain an origin address and a destination address, based on which local routing decisions are made. This is also referred to as routing on a per hop basis, in other words routers forward to a subsequent node (next hop) based on the destination address specified in
- 25 the data packet. Conventional IP technology has the significant advantage that states do not have to be maintained in the network and paths do not have to be determined beforehand for the transmission of data packets. This has to be offset against the disadvantage that the packets can only be switched on a
- 30 "best effort" basis, i.e. there is no guarantee of quality of service.

The most commonly used routing protocol for an autonomous network domain or autonomous system at present is the so-called OSPF (Open Shortest Path First) protocol, which utilizes a distributed routing approach. The topology of the network is  
5 thereby known to the every node and is distributed by so-called link state advertisement messages to all the nodes in the network. The shortest path in each instance is calculated autonomously in every node for all the destinations known to said node based on link metrics. Link failure results in re-  
10 calculation of the paths.

Two main approaches are followed to improve the quality of service of IP networks in respect of new services with quality of service requirements. With one approach more than one path  
15 is established between a source and a drain or an origin and a destination, in order to be able to respond to bottleneck situations or fault situations by distribution via different paths. The routing protocol OSPF has been extended to this end by introducing the Equal Cost Multipath (ECMP) concept, which  
20 allows the simultaneous use of a number of paths of equal length, in the sense of a metric, between a source and a drain. The method makes it possible to distribute the traffic to paths of the same length. An extension of this concept can be understood to be the optimization of link usage based on  
25 measured or calculated network loads using traffic engineering mechanisms, i.e. mechanisms to control and regulate the packet traffic. The so-called OSPF-TE (TE: Traffic Engineering) method tries to allow regular distribution of the traffic in the network by adjusting the link metrics distributed in the  
30 network as a function of the usage of the respective link. The multipath routing methods are typically based on a central load distribution calculation, i.e. a decision is made at a central

point or by a central entity about how the packets should be distributed.

The second approach is the central determination of paths through the network along with permanent reservation of the required bandwidth. The most important concept, involving the switching of paths, is the so-called Multi Protocol Label Switching (MPLS) protocol or concept. Virtual paths through the network are defined in the context of this concept. Incoming packets are allocated to virtual paths at the input router of an MPLS domain. Appropriate global selection of the paths and the assignment of packets to the paths allow regular distribution in the network.

Such approaches to improving the transmission quality of conventional data networks to some extent at least cancel out the advantages of conventional data networks, namely their flexibility and low level of complexity.

The object of the invention is to specify a method for multipath routing, with which traffic distribution or load distribution is optimized whilst avoiding the disadvantages of conventional methods.

The object is achieved by claims 1 and 9.

The method is based on a packet-based network, in which there is provision for multipath routing or the distribution of packets to different paths. The network is made up of nodes and links (also referred to as edges or connection segments). It is possible, for some of the nodes at least, to send incoming packets to their destination on a number of different paths. The term array of paths or distribution array is used below for

the different alternatives or different options for a node to forward a data packet to a subsequent link as a function of the destination of the data packet. The array of paths for a node in respect of a destination comprises the links out of the  
5 node, via which packets can be routed to the destination. The paths to the destination do not necessarily have the same length in the sense of a metric. A destination is generally defined by the routing criterion for the individual nodes specified in a routing table. This is not necessarily identical  
10 to the destination address generally specified in the packet but can, for example, comprise part of the destination address. In the case of IP networks the nodes or routers generally use the part of the address describing the network, in which the IP network end point (e.g. host gateway) is located, which  
15 corresponds to the full destination address of the packet.

According to the invention, nodes in the network independently or autonomously distribute the packets or the load to the links of an array of paths. This load distribution is also changed  
20 autonomously by the nodes. A node monitors the traffic load or packet rate it routes to a link. If an overload occurs in a link, this is detected by the node and an overload protection measure is then initiated. The primary overload protection measure is to redistribute traffic from the overloaded link to  
25 other links in the associated array of paths. A response to a link failure by redistributing to links of the associated array of paths that have not failed can be provided for correspondingly.

30 The invention has the advantage that the overload protection response by the node is autonomous, i.e. redistribution takes place locally. There is no need for a complex signaling operation or the propagation of messages through the entire

network of nodes, which would very significantly increase the complexity of the routing protocol. Nor is there a need for a central entity, either for control purposes or to determine weightings if node weightings should have to be recalculated.

5 Instead the weightings for routing purposes along an array are once again determined by the respective nodes. A central control entity is a weak point in respect of any fault in said entity and this is avoided in the present invention.

10 The inventive redistribution or allocation of the traffic to different paths can be infinite in the sense that any allocation ratios of packets to links of an array of paths are possible. This contrasts with various current multipath routing methods (e.g. ECMP), which specify a fixed allocation ratio.

15 Optimum allocation ratios can for example be determined using the traffic matrix, i.e. the measured or calculated traffic loads on the links. Alternatively it is possible to optimize allocation ratios by means of a control process. The modified link loads in the event of traffic redistribution are thereby  
20 related to the traffic redistribution measures and the distribution measures to avoid overload situations are thereby determined.

According to one development, load redistribution is carried  
25 out by the individual nodes or by one individual node in stages. No further traffic redistribution measures are thereby implemented after the end of a stage during a waiting period or a time interval. After the end of the time interval any next stage that may be required for traffic redistribution is  
30 started. This allows the nodes following after a node initiating a protection measure to resolve any overload resulting at them due to the redistribution and to redistribute

the traffic in turn. Also gradual load adjustment counteracts system oscillation.

The subject matter of the invention can be developed for  
5 situations, in which the overload cannot be resolved by  
redistribution within an array or if a link fails the data  
packets cannot be distributed to the other links of the  
associated array of paths, without generating an overload on  
one of these links. To this end an overloaded node sends a  
10 message to one node upstream from it at least, prompting said  
node to carry out a redistribution operation for its part, such  
that fewer data packets are transmitted to the node in  
question. Upstream thereby relates to the paths of the packets  
distributed on the distribution arrays affected by the overload  
15 or link failure. This method can be extended recursively or in  
a cascaded fashion to the upstream nodes in front of the node  
in question, such that every node that receives a message  
requesting redistribution but cannot achieve this by  
redistribution within the array or arrays for its part sends  
20 messages to nodes upstream from it, so that these for their  
part reduce the traffic by redistribution. It is thereby  
expedient for a message prompting redistribution to contain  
information about the required traffic reduction, e.g. its  
nature and scope. This method generally reaches a limit when an  
25 edge node in the network receives a message to reduce the  
overload. For edge nodes can generally not communicate with  
nodes in another network using the protocol used within the  
network to transmit messages. To reduce the traffic going away  
from it, such an edge node can reduce the traffic it allows  
30 into the network as part of a network access control, to bring  
about the required traffic load reduction in this fashion.  
Access controls are frequently used in data networks, which are

intended to ensure transmission in compliance with quality of service features.

The subject matter of the invention also includes a network node or router, which is equipped [with means to identify] a traffic overload and to redistribute traffic to other links going out from nodes. Such a node can also be provided with means to send messages, said messages being able to bring about traffic redistribution in upstream nodes. These means for example include software modules, which support the protocol used to send the messages.

The subject matter of the invention is described in more detail below based on an exemplary embodiment with reference to two figures, in which:

Figure 1 shows a network segment with nodes and links

Figure 2 shows an associated table with details of distribution arrays assigned to the nodes shown in the network segment.

Figure 1 shows nodes 1 to 6 and links (connections between the nodes) LIJ, I, J out from (1, 2, 3, 4, 5, 6, 7). A direction is thereby assigned to a link. For example the link L31 goes from the node 3 to the node 1. The overall traffic on the associated physical link between the nodes 3 and 1 is therefore made up of the traffic on the link L31 and the link L13, if there is provision for sending packets from the node 1 to the node 3. For the sake of simplicity links are only shown with one direction in the figure. Figure 2 shows a table with different arrays of paths going out from the node 3. The first column D shows the destination or drain of packets forwarded from the

node 3. For simplicity it is assumed that each of the other nodes shown is a possible destination for the packets sent. The second column shows the arrays of paths WF to the respective destinations. For example an array comprising three links is defined to the destination defined by the node 1, one link leading directly to the node 1 and the other two respectively via the nodes 2 and 7. The distribution ratio R or load distribution on these distribution arrays or arrays of paths is shown in the third column of the table. 70% of the traffic is thus routed directly to the node 1, while the other 30% is sent via the node 2, or the node 7 to its destination, the node 1. The distribution arrays to the nodes 2, 4, 5, 6 and 7 are shown in a similar fashion. The distribution ratio was determined according to the path priorities, with direct links having a higher distribution weighting. If the link L31 between the node 3 and the node 1 now fails, according to the invention the node 3 can distribute the traffic to the node 1 via the nodes 2 and 7 by changing the distribution weightings accordingly. As the majority of the traffic was sent via the link L13 between the node 1 and the node 3, redistribution can cause an overload on the links L37 between the node 3 and the node 7 and L32 between the node 3 and the node 2. To reduce this overload, the node 3 sends a message to the node 4 and the node 5, to reduce the traffic routed to it. On receipt of this message the nodes 4 and 5 change their traffic distribution for packets to the destination defined by the node 1. For example the node 5 routes a larger proportion of the traffic to the node 1 via the nodes 6 and 7 instead of via the node 3. And the node 4 increases the proportion of traffic routed via the node 2 to the node 1. This results in a reduction of the load on the links L37 and L32 between the nodes 3 and 7 and 3 and 2, in that upstream nodes, namely 5 and 4, route more traffic via the links L54, L42, and L21, as well as L56, L67 and L71. In actual



networks with very many more nodes, the node 5 would generally have a node upstream from it, to which it could in turn send a message, if the measure taken by it would not result in the necessary reduction in traffic volume.

## Claims

1. Method for redistributing traffic in response to a traffic overload or link failure in a packet-based network made up of  
5 nodes (1, 2, 3, 4, 5, 6, 7) and links (L31, L32, L37, L71, L21, L42, L43, L67, L53, L54, L56) with multipath distribution of packets, with packets with the same destination being able to be distributed to at least two links, which are associated with an array of paths (L31, L32, L37) assigned to the destination,  
10 at least for some of the nodes, according to which
  - a node (3) determines when the traffic load on a link (L31) going away from it exceeds an upper limit or a link (L31) going away from it fails,
  - 15 - the node (3) redistributes the traffic load independently of external control entities, by routing at least some of the packets, which would have been routed via the outward link (L31) had the load distribution not been changed, to one or more other links (L32, L37) going away from the node (3), which  
20 are assigned to the same array of paths (L31, L32, L37).
2. Method according to claim 1, characterized in that
  - the traffic load redistribution is carried out in stages in  
25 respect of proportions of the overload and
  - at the end of a stage there is a waiting period of a time interval before the next stage is initiated.
3. Method according to claim 1 or 2,  
30 characterized in that
  - if the traffic load does not drop below the upper limit as a result of the traffic redistribution without a different upper limit being exceeded on a link going away from the node, a

message is sent to a node (4, 5) that is upstream in respect of packets distributed via the arrays of paths (L31, L32, L37), which causes a traffic load redistribution at this upstream node (4, 5) to reduce the traffic load sent by the [lacuna] to the [lacuna] and distributed via the arrays of paths (L31, L32, L37).

4. Method according to claim 3, characterized in that

- 10 - a message is sent to all nodes (4, 5) directly upstream in respect of packets distributed via the arrays of paths (L31, L32, L37) for the purpose of traffic redistribution at these upstream nodes to reduce the traffic load sent by the [lacuna] to the [lacuna] and distributed via the arrays of paths (L31, L32, L37).

5. Method according to claim 3 or 4, characterized in that

- 20 - the message contains information about the required traffic load reduction.

6. Method according to one of claims 5, characterized in that

- 25 - a notified upstream node (4, 5), which cannot achieve the required traffic load reduction for the node in question by means of traffic load redistribution without causing a further upper limit for a traffic load to be exceeded, for its part sends a message to a node upstream from it, prompting said node to carry out the required traffic load reduction by traffic redistribution or by sending messages to upstream nodes.

7. Method according to claim 6, characterized in that

- upstream nodes, which receive a message from the node in question (3) or from an upstream node (4, 5) either carry out the traffic load reduction required according to the message received by traffic load redistribution or send at least one  
5 message to an upstream node to reduce the traffic load,

8. Method according to one of claims 3 to 6, characterized in that

- an edge node, which receives a message to reduce the traffic  
10 load at an upstream node, brings about the required traffic load reduction by reducing the limits for controlling access to the network.

9. Node (3) for a packet-based network with multipath  
15 distribution, with

- means for identifying a traffic overload on a link going away from it and  
- means for redistributing traffic to other links going away from the node (3) and associated with the same distribution  
20 array.

10. Node (3) according to claim 9, with

- means for sending messages to a node (4, 5) that is upstream  
25 in respect of packets sent via the distribution arrays (L31, L32, L37) to request a traffic reduction in the traffic transmitted from the upstream node (4, 5).